

Technical Details

	Natural Gas	Propane
Heat Input	9.3kW (31700 Btu/h)	9.0kW (30700 Btu/h)
Heat Output	7.7kW (26000 Btu/h)	7.7kW (26000 Btu/h)
Gross Efficiency	82.0%	84.7%
Min. wall thickness	50mm (standard)	50mm (standard)
Max. wall thickness	1000mm (long flue)	1000mm (long flue)
Gas Connection	Rc ½ (½" BSP int.)	Rc ½ (½" BSP int.)
Flue hole size	110mm diameter	110mm diameter
Colour	Shades of Grey	Shades of Grey
Electrical Supply	230V 50Hz AC	230V 50Hz AC
Certificate no.	BG/EC-87/96/275	BG/EC-87/96/275
Clearances req'd	Top 200mm Front 600mm LHS 100mm RHS 600mm	Top 200mm Front 600mm LHS 100mm RHS 600mm



Vulcana Gas Appliances Ltd
Bridge Road, Haywards Heath
West Sussex RH16 1TX
Telephone: (01444) 415871
Fax: (01444) 441433
e-mail vulcanagas@pavilion.co.uk
web www.vulcanagas.co.uk

All specifications are subject to alteration without prior notice.

The Kestrel 26



The **Kestrel 26** is the latest addition to the Temcana range, catering for those applications where lower cabinet temperatures are required.

Giving 7.7kW (26,000 Btu/h) output, the **Kestrel 26** has the same dimensions and connections as the Kestrel 55 and uses the same cabinet.

When fitted with its specially made heater guard the **Kestrel 26** produces a maximum temperature rise of 46°C, with by far the greatest area being below 35°C rise.



Vulcana Gas Appliances Ltd
Bridge Road, Haywards Heath, West Sussex RH16 1TX
Telephone (01444) 415871 Fax: (01444) 441433
e-mail vulcanagas@pavilion.co.uk
web www.vulcanagas.co.uk